

Corrugated tube



F143-3422

Application

This corrugated tube is designed to protect and insulate electrical cables and wires.

Description

- They are available in black and/or grey.

Reference	F14X-2321	F14X-3422
Materials	Polyethylene	Polyolefin
Crushing strength (in N)	320 N	750 N
Impact resistance (in J)	2 J	6 J
Operating temperature (in °C)	-5°C / +60°C	-5°C / +90°C
Presence of thread pullers	✓	✓
UV protection	✗	✗

Code	Designation	External diameter (in mm)	Minimal internal diameter (in mm)	Weight (kg)	Sales unit
ICTA 2321					
F140-2321	RINGED TUBE DIAMETER 16 (100m)	16	11.2	2.800	1
F141-2321	RINGED TUBE DIAMETER 20 (100m)	20	13.7	3.600	1
F142-2321	RINGED TUBE DIAMETER 25 (50m)	25	18.7	2.700	1
F143-2321	RINGED TUBE DIAMETER 32 (50m)	32	24.8	3.500	1
F144-2321	RINGED TUBE DIAMETER 40 (50m)	40	31.6	4.300	1
F145-2321	RINGED TUBE DIAMETER 50 (50m)	50	39.8	5.400	1
ICTA 3422					
F140-3422	RINGED TUBE DIAMETER 16 (100m)	16	10.7	2.800	1
F141-3422	RINGED TUBE DIAMETER 20 (100m)	20	14.1	3.600	1
F142-3422	RINGED TUBE DIAMETER 25 (100m)	25	18.3	2.500	1
F143-3422	RINGED TUBE DIAMETER 32 (50m)	32	24.3	3.700	1
F144-3422	RINGED TUBE DIAMETER 40 (50m)	40	31.2	3.000	1
F145-3422	RINGED TUBE DIAMETER 50 (50m)	50	39	3.000	1
F146-3422	RINGED TUBE DIAMETER 63 (50m)	63	47	7.000	1